


## HDMI TYPE-A RECEPTACLES - RIGHT ANGLE SMT - STANDARD

### Features:


- Up to 18 Gbps communication speed
- Industry standard plug and play technology - 'Hot Pluggable'
- Compatible with synchronous and asynchronous data transfer
- Data and power combined in one small package
- RoHS compliant



### Specifications:

Insulator Material	Thermoplastic UL-94V-0
Contact Material	Copper alloy
Contact Plating	Nickel under plating with Gold plating on contact areas
Shell Material	Copper alloy with Nickel plating
Insertion Force	44N maximum
Withdrawal Force	10N minimum to 39N maximum

### EXAMPLE PART NUMBER: 694D119E264-011



#### Series:

694D Receptacle

#### Connector Type:

119 HDMI Type-A

#### Special Option:

- Standard

E EMI Fingers - (Mounting Opt 4 & Connector Opt 0 Only)

#### Contact Plating:

1 2µ" ~ 5µ" Gold

2 Gold Flash

3 5µ" ~ 10µ" Gold

5 15µ" Gold

6 30µ" Gold

#### Contact Code / Mounting Orientation:

6 Right Angle SMT

#### Mounting Option:

3 4 Through Hole Grounding Tabs 1.4mm ± 0.25

4 4 Through Hole Grounding Tabs 1.95mm ± 0.25

5 4 Through Hole Grounding Tabs 2.5mm ± 0.25

8 4 Through Hole Grounding Tabs MIXED LENGTHS

#### Connector Option:

0 Standard Body

1 Raised Off PCB <3mm - (Mounting Options 3 & 4 Only)

2 Raised Off PCB >3mm - (Mounting Option 5 Only)

4 Short Body - (Mounting Option 4 Only)

#### Material:

1 LCP

#### Insulator Color:

1 Black

#### Ordering Code Notes:

Not all part numbers deriving from this ordering guide will be available.

Some may be available upon request. Please first consult the website, if the connector is not readily available then please contact EDAC's customer service for further inquiries.