

## ELECTRICAL CHARACTERISTICS

| Part No.               | Working Voltage (Vw) | Clamping Voltage (Vc) | ESD Withstanding | Capacitance (C) |      | Capacitance Tolerance |
|------------------------|----------------------|-----------------------|------------------|-----------------|------|-----------------------|
|                        | Volts                | Volts                 | Times            | pF              |      | %                     |
|                        | <15 $\mu$ A          | 1A,8/20 $\mu$ s       | 8KV*             | 1KHz            | 1MHz |                       |
| <b>JMV0402C240T4R7</b> | 24                   | 130                   | > 1000           | -               | 4.7  | -20% ~ +80%           |
|                        |                      |                       |                  |                 |      |                       |
|                        |                      |                       |                  |                 |      |                       |

\* - In system ESD withstanding pulse per IEC 61000-4-2, 8KV, contact discharge method.

Vw- The max. steady state DC operating voltage of which varistor could maintain also not exceeding 15uA leakage current.

Vc- The peak voltage acrossed the varistor measured at a specified pulse current and waveform.

C - The device capacitance measured with 1.0Vrms, 1KHz / 0.5rms, 1 l

MLV Storage condition → Temperature:  $\leq 30^{\circ}\text{C}$  / Humidity :  $\leq 60\%$  RH (Moisture Sensitivity Levels: 2a)

MLV Preservation period → 6 months

## External Dimension

Chip Dimension

| Chip Size      | inch(mm)                               |  |                        |  |
|----------------|--|--|------------------------|--|
|                | L                                      | W                                      | T                      | A                                      |
| 0402<br>(1005) | 0.040 $\pm$ 0.004<br>(1.00 $\pm$ 0.10) | 0.020 $\pm$ 0.004<br>(0.50 $\pm$ 0.10) | 0.024max.<br>(0.6max.) | 0.010 $\pm$ 0.006<br>(0.25 $\pm$ 0.15) |

