

## AC/AC POWER SUPPLY LINEAR

- Fixed output voltages
- Thermal fuse in transformer
- Mains cord
- Cord or snap terminals
- Mounting bracket available



- Faste utgangsspenninger
- Termosikring i transformator
- Nettledning
- Sekundærledning eller snappkontakt
- Kan leveres med festebrakett

Technical specifications	Tekniske data		6820	8930
Input voltage:	Inngangsspenning:	VAC	230 VAC +6/-10%, 50/60Hz	
Output voltage:	Maks. utgangseffekt:	VA	25	31
Temperature range:	Temperaturområde:	C	-20 °C - +30 °C	
Insulation class:	Isolasjonsklasse:		II	
Insulation voltage:	Isolasjonsspenning:	VAC	3000	3750
Electrical safety standard:	Elektrisk sikkerhetsstandard:		EN 60950	EN 60950
EMC standards	EMC standarder			EN 60742
• Emission:	• Emisjon:		EN 61000-6-3	
• Immunity:	• Immunitet:		EN 61000-6-1	
Dimensions:	Mål:	LxWxH mm	98x87x55	98x87x55
Weight:	Vekt:	g	920	950

### Voltage versions / Spenningsversjoner

VAC	Maks. last / Max. load (A)	
	6820	8930
3	5,0	
4,5	5,0	
5	5,0	
6	4,1	5,0
7,5	3,3	4,1
9	2,7	3,4
12	2,0	2,5
15	1,6	2,0
18	1,4	1,7
21	1,2	1,4
24	1,0	1,2
36		0,86
42	0,6	0,73

Individual data sheets are available at [www.mascot.com](http://www.mascot.com)  
 Individuelle dataark er tilgjengelige på [www.mascot.com](http://www.mascot.com)