


- Plug-in unit
- Fixed output voltages
- Thermal fuse in transformer and thermal protection in the regulator
- Exchangeable output plugs
- Plugg-inn enhet
- Faste utgangsspenninger
- Termosikring i transformator og termisk beskyttelse i regulator
- Utskiftbare plugger



Technical specifications

Input voltage:
Output voltage:
Max. output power:
Ripple:
Insulation class:
Electrical safety standard:
EMC standards
• Emission:
• Immunity:
Output terminals
Cord with/without plug:
Dimensions excl. plug (LxWxH):
Weight:

Tekniske data

Inngangsspenning: 230 VAC +6/-10%, 50/60Hz
Utgangsspenning: 5-24 VDC
Maks. utgangseffekt: 4,8 W
Rippel: < 30 mV p-p
Isolasjonsklasse: II
Elektrisk sikkerhetsstandard: EN 60065, EN 60950
EMC standarder
• Emisjon: EN 61000-6-3
• Immunitet: EN 61000-6-1
Utgangsterminaler
Sek. ledning med/uten plugg: Accessories /Tilbehør
Mål uten plugg (LxBxH): 95 x 51 x 57 mm
Vekt: 420 g

Voltage version (VDC) Spenningsversjoner (VDC)	Nominal load (mA) Merkelast (mA)
5	700
6	600
7,5	600
9	500
12	400
15	340
18	280
24	210