


- Plug-in unit
- Secondary switch mode technique
- Stepless adjustable output voltage 5-24 VDC
- Thermal fuse in transformer and thermal protection in the regulator
- Exchangeable output plugs
- Plugg-inn enhet
- Sekundærsvitsjet
- Trinnløs justerbar utgangsspenning fra 5-15 VDC
- Termosikring i transformator og termisk beskyttelse i regulator
- Utskiftbare plugger



**Technical specifications**

Input voltage:  
Output voltage:  
Max. output power:  
Insulation class:  
Electrical safety standard:  
EMC standards  
• Emission:  
• Immunity:  
Output terminals  
Cord with/without plug:  
Dimensions excl. plug (LxWxH):  
Weight:

**Tekniske data**

Inngangsspenning: 230 VAC +6/-10%, 50/60Hz  
Utgangsspenning: 5-24 VDC  
Maks. utgangseffekt: 10 W  
Isolasjonsklasse: II  
Elektrisk sikkerhetsstandard: EN 60065, EN 60950  
EMC standarder  
• Emisjon: EN 61000-6-3  
• Immunitet: EN 61000-6-1  
Utgangsterminaler  
Sek. ledning med/uten plugg: Accessories /Tilbehør  
Mål uten plugg (LxBxH): 100 x 51 x 63 mm  
Vekt: 450 g

