

ELECTRICAL CHARACTERISTICS

Part Number	Working Voltage (Vw)	Breakdown Voltage (Vb)	Clamping Voltage (Vc)	Peak Current (Ip)	Transient Energy (Et)	Typical Capacitance (C)	
	Volt	Volt	Volt	Amp	Joule	pF	
	<50 μ A	1mA(DC)	2.5A,8/20 μ s	8/20 μ s	10/1000 μ s	1KHz	1MHz
JMV1206S480T251	48	55.8~68.2	100	100	0.8	250	-

Vw- The max. steady state DC operating voltage of which varistor could maintain also not exceeding 50uA leakage current.

Vb- The Voltage acrossed the device measured at 1mA DC current.

Vc- The peak voltage acrossed the varistor measured at a specified pulse current and waveform.

Ip- The max.peak current applied with specified wavefoem without any possibility of device fail.

Et- The max. energy which dissipated with the specified waveform without any possibility of device fail.

C - The device capacitance measured with zero volt bias, 1.0Vrms and 1KHz / 0.5 V rms and 1 MHz.

MLV Storage condition → Temperature: $\leq 30^{\circ}\text{C}$ / Humidity : $\leq 60\%$ RH (Moisture Sensitivity Levels: 2a)

MLV Preservation period → 6 months

External Dimension

Chip Dimension

Chip Size	inch(mm)			
	L	W	T	A
1206 (3216)	0.126±0.008 (3.20±0.20)	0.063±0.008 (1.60±0.20)	0.071max. (1.8max.)	0.028max. (0.71max.)

