

LED DOT MATRIX
BL-M12X591
Features:

- Ø 36.00mm (1.4") 4.0x4.0 SQUARE dot matrix LED display.
- Ø Low current operation.
- Ø Excellent character appearance.
- Ø Easy mounting on P.C. Boards or sockets.
- Ø I.C. Compatible.
- Ø ROHS Compliance.


Super Bright
Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=20mA)

Part No			Chip			VF Unit:V		Iv
Row Cathode	Column Anode	Row Anode	Emitted Color	Material	λ_p (nm)	Typ	Max	TYP.(mcd)
BL-M12A591S-XX		BL-M12B591S-XX	Hi Red	GaAlAs/GaAs,SH	660	1.85	2.20	105
BL-M12A591D-XX		BL-M12B591D-XX	Super Red	GaAlAs/GaAs,DH	660	1.85	2.20	115
BL-M12A591UR-XX		BL-M12B591UR-XX	Ultra Red	GaAlAs/GaAs,DDH	660	1.85	2.20	125
BL-M12A591E-XX		BL-M12B591E-XX	Orange	GaAsP/GaP	635	2.10	2.50	95
BL-M12A591Y-XX		BL-M12B591Y-XX	Yellow	GaAsP/GaP	585	2.10	2.50	95
BL-M12A591G-XX		BL-M12B591G-XX	Green	GaP/GaP	570	2.20	2.50	100

Ultra Bright
Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=20mA)

Part No		Chip			VF Unit:V		Iv
Row Cathode	Column Anode	Emitted Color	Material	λ_p (nm)	Typ	Max	TYP.(mcd)
BL-M12A591UHR-XX	BL-M12B591UHR-XX	Ultra Red	AlGaInP	645	2.10	2.50	125
BL-M12A591UE-XX	BL-M12B591UE-XX	Ultra Orange	AlGaInP	630	2.10	2.50	105
BL-M12A591YO-XX	BL-M12B591YO-XX	Ultra Amber	AlGaInP	619	2.10	2.50	105
BL-M12A591UY-XX	BL-M12B591UY-XX	Ultra Yellow	AlGaInP	590	2.10	2.50	105
BL-M12A591UG-XX	BL-M12B591UG-XX	Ultra Green	AlGaInP	574	2.20	2.50	135
BL-M12A591PG-XX	BL-M12B591PG-XX	Ultra Pure Green	InGaN	525	3.80	4.50	155
BL-M12A591B-XX	BL-M12B591B-XX	Ultra Blue	InGaN	470	2.70	4.20	75
BL-M12A591W-XX	BL-M12B591W-XX	Ultra White	InGaN	/	2.70	4.20	105

--XX: Surface / Lens color :

Number	0	1	2	3	4	5
Ref Surface Color	White	Black	Gray	Red	Green	
Epoxy Color	Water clear	White diffused	Red Diffused	Green Diffused	Yellow Diffused	

Absolute maximum ratings (Ta=25°C)

LED DOT MATRIX
BL-M12X591

Parameter	S	D	UR	E	Y	G	Unit
Forward Current I_F	25	25	25	25	25	30	mA
Power Dissipation P_d	60	60	60	60	60	65	mW
Reverse Voltage V_R	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	150	150	150	150	150	150	mA
Operation Temperature T_{OPR}	-40 to +80						°C
Storage Temperature T_{STG}	-40 to +85						°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)						°C

Absolute maximum ratings (Ta=25°C)


Parameter	UHR	UE	YO	UY	UG	PG	B	W	Unit
Forward Current I_F	30	30	30	30	30	30	30	30	mA
Power Dissipation P_d	75	65	65	65	75	110	120	120	mW
Reverse Voltage V_R	5	5	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	150	150	150	150	150	150	100	100	mA
Operation Temperature T_{OPR}	-40 to +80								°C
Storage Temperature T_{STG}	-40 to +85								°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)								°C

LED DOT MATRIX


BL-M12X591

Package configuration & Internal circuit diagram


BL-M12X591 Series



BL-M12A591



BL-M12B591




Notes:

1. All dimensions are in millimeters (inches)
2. Tolerance is $\pm 0.25(0.01)$ unless otherwise noted.
3. Specifications are subject to change without notice.


LED DOT MATRIX

BL-M12X591


Typical electrical-optical characteristics curves:



- | | |
|---|--------------------------------------|
| (1) - GaAsP/GaAs 655nm/Red | (9) - GaAlAs 880nm |
| (2) - GaP 570nm/Yellow Green | (10) - GaAs/GaAs & GaAlAs/GaAs 940nm |
| (3) - GaAsP/GaP 585nm/Yellow | (A) - GaN/SiC 430nm/Blue |
| (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red | (B) - InGaN/SiC 470nm/Blue |
| (5) - GaP 700nm/Bright Red | (C) - InGaN/SiC 505nm/Ultra Green |
| (6) - GaAlAs/GaAs 660nm/Super Red | (D) - InGaAlSiC 525nm/Ultra Green |
| (8) - GaAsP/GaP 610nm/Super Red | |



FORWARD VOLTAGE (Vf)
FORWARD CURRENT VS.
FORWARD VOLTAGE



FORWARD CURRENT (mA)
RELATIVE LUMINOUS
INTENSITY VS. FORWARD
CURRENT




AMBIENT TEMPERATURE Ta (°C)
FORWARD CURRENT VS. AMBIENT
TEMPERATURE



AMBIENT TEMPERATURE Ta (°C)



tp-PULSE DURATION μ s
(1,2,3,4,6,8,B,D,J,K)



tp-PULSE DURATION μ s
(5)

NOTE:25 free air temperature unless otherwise specified