



| Type No. | Resistance at 25°C | Tolerance | I max. | RI max. | Thermal Dissipation Coefficient | Thermal Time Constant | Maximum Capacitance AC(uF) | B _{25/50} Value |
|----------|--------------------|-----------|--------|---------|---------------------------------|-----------------------|----------------------------|--------------------------|
| | (Ohms) | % | (Amps) | (Ω) | (mW/°C) | (sec.) | (240V) | (±10%) (°K) |
| 15S050M | 5 | ±20 | 6.0 | 0.128 | 25 | 110 | 390 | 2850 |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Material of coating : Silicone

Color of coating : Green

Storage condition → Temperature: -40°C~125°C/ Humidity : 75%RH max. Status

Preservation period → 12 months

Operation temperature range : φ 8 ~ φ 10 : -40°C ~ 170°C

φ 13 ~ φ 20 : -40°C ~ 200°C

Lead style :

P : Straight type

Y : Kink type



DIMENSION :

(unit:mm)

| Type No. | D max. | T max. | L min | F±1.0 | d±0.05 | H max |
|----------|--------|--------|-------|-------|--------|-------|
| 15S050M | 17.5 | 6.5 | 24.0 | 7.5 | 0.8 | 23.0 |
| | | | | | | |
| | | | | | | |
| | | | | | | |